



Anti-Spatter for Welding (W506)

Ideal for professional use but can also be used by DIY welders. This product is free of silicone substance. It prevents the formation of rust, protects from humidity, and prevents seize of welding spatter.



ANTI-SPATTER FOR WELDING – A product made of film forming synthetic polymers. Due to their special features, it prevents the seizure of welding spatter to any surface. The film also prevents oxidation and corrosion caused by chemicals. It is suitable for autogenous, electric and inert-gas welding. The compound is free of silicon substances.

Technical specifications:

Barcode	EAN: 8034108890517
Quantity	400 ml – Net Wt. 7.9 oz 226 g
Case	12 pieces
Aspect	Cylinder containing under pressure fluid
Color	straw yellow
Odor	Typical of solvent
Relative density	At 68°F 0.55 ÷ 0.59 g/ml
Flash point	Low. 32° F
Pressure a 68°F	3/5 bar
Vapor pressure	< 0.01 hPa a 68°F
Vapor density(air=1)	9-12
Viscosity at 122°F	(ASTM D 445) 11 ÷ 24 cst
Solubilità	Insoluble in water
Autoignition temperature	>752°F(dry residual)
Corrosion on copper	(ASTM D 130): 1

HOW TO USE: Before the application carefully clean and degrease the surfaces to be treated. Shake well before use. Point and spray on the parts to be treated. When applying to metal surfaces spray from a distance of 8-10 inches in a sweeping motion. Wipe clean when finished.

STORAGE

Before using: stock the product in a dry location above 32°F degrees and below 113°F. After use, keep containers closed. In the original package, the product can be conserved for 24 months.

After the first use: conserve in a fresh and dry location, away from hot conditions. Keep out of reach of children.

Hazards identification:

H222	Extremely flammable aerosol.
H229	Pressurized container: may burst if heated.

This information, even if reliable, must be considered only approximate. We are not responsible for the wrong use of the product, or the violation of any license. Before using, the users should verify the suitability of the product for its specific use.