



Cutting Oil (OL104)

This Ambro-Sol spray is ideal for hard metal cutting applications. It's perfect for hydraulic and steel sectors.



HOW TO USE: Shake and spray directly on the parts to be treated. This product can also be used with the straw attached to the cap.

Quantity	400 ml – Net Wt. 10.3 oz 293 g
Barcode	EAN 13: 8034108890159
Case	12 pieces

CUTTING OIL – HEAVY-DUTY PROTECTIVE TOOL LUBRICANT. Developed for professional applications in hard metal cutting operations. This oil has a paraffin mineral base, enriched with special EP anti-weld additives. Ideal for use in difficult threading operations with particularly hard, alloy steel. Can also be used with other types of metals including brass copper and aluminum. Suited for use in the hydraulic sector.

Technical Specifications:

Aspect	Cylinder containing under pressure fluid
Color	Light brown
Odor	Characteristic of solvent
Relative density	a 68°F 0.64 ÷ 0.68 g/ml
Flash point	Low. 32° F
Pressure at 68°F	4/6 bar
Pour point	< 14°F
Viscosity Oil at 104°F	288 - 352 cst
Max temperature	>572°F(Oil Content)
Initial boiling point	>482°F(at atmosferic pressure)

STORAGE

Before using: stock the product in a dry location above 32°F degrees and below 113°F. After use, keep containers closed. In the original package, the product can be conserved for 24 months.

After the first use: conserve in a fresh and dry location, away from hot conditions. Keep out of reach of children.

Hazards identification:

H222	Extremely flammable aerosol.
H229	Pressurized container: it may burst if heated.
H315	Causes skin irritation.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.

This information, even if reliable, must be considered only approximate. We are not responsible for the wrong use of the product, or the violation of any license. Before using, the users should verify the suitability of the product for its specific use.