



Lithium Grease (G001)

This grease is perfect for everyday use and lubrication. Ideal for all around use in the home, automotive, agriculture and industry. Great for metal on metal lubrication and in the presence of salty or dirty atmospheric conditions.



Quantity	400 ml - Net wt.10.4 oz 297 g
Barcode	EAN 13: 8034108890005
Case	12 pieces

LITHIUM GREASE – A high quality grease that has a wide spectrum of uses and good chemical stability. Great for metal on metal lubrication. Water-repellent and resistant to salty or dirty atmospheric conditions. Ideal for lubricating bearings, bushes, hubs, kingpins, guide rails, chains, cables and for general all-around use in the home, motor vehicles, agriculture and industrial machinery.

Technical Specifications:

Aspect	Cylinder containing under pressure fluid
Color	Light brown
Odor	Characteristic of solvent
Relative density	a 68°F 0.61 ÷ 0.65 g/ml
Flash point	Low. 32° F
Pressure at 68°F	4/6 bar
Consistency	NLGI EP2 (soap of lithium base)
Penetration at 77°F 0.1 mm	265-295
Drip point	+ 356°F
Application temperature	-40°F - +338°F

HOW TO USE: Shake and spray directly on the parts to be treated. This product can also be used with the straw attached to the cap.

STORAGE

Before using: stock the product in a dry location above 32°F degrees and below 113°F. After use, keep containers closed. In the original package, the product can be conserved for 24 months.

After the first use: Store in a fresh and dry location, away from hot conditions. Keep out of reach of children.

Hazards identification:

H222	Extremely flammable aerosol.
H229	Pressurized container: may burst if heated.
H315	Causes skin irritation.
H336	May cause drowsiness or dizziness
H411	Toxic to aquatic life with long lasting effects

This information, even if reliable, must be considered only approximate. We are not responsible for the wrong use of the product, or the violation of any license. Before using, the users should verify the suitability of the product for its specific use.