

Safety Data Sheet

1. Identification

1.1. Product identifier

Code: W508/USA
Product name: Ceramic Based Anti-Spatter shield
Chemical name and synonym: Anti spatter

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use: Not regulated

Identified Uses	Industrial	Professional	Consumer
Industrial Use	✓	-	-
Professional Use	-	✓	-

1.3. Details of the supplier of the safety data sheet

Name: AMBRO-SOL S.R.L.
Full address: Via per Pavone del Mella n.21
District and Country: 25020 Cigole (BS)
Italia

Tel. +39 030 9959674

Fax +39 030 959265

e-mail address of the competent person

responsible for the Safety Data Sheet: quality@ambro-sol.com

1.4. Emergency telephone number

For urgent inquiries refer to

American Association of Poison Control Centers: +1 (800) 222-1222

2. Hazards identification

Note: This product is a consumer product and is labeled in accordance with the US Consumer Product Safety Commission regulations which take precedence over OSHA Hazard Communication labeling. The actual container label will not include the label elements below. The labeling below applies to industrial/professional products.

2.1. Classification of the substance or mixture

The product is classified as hazardous pursuant to the provisions set forth in OSHA Hazard Communication Standard (HCS) (29 CFR 1910.1200). The product thus requires a safety datasheet.

Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Classification and Hazard Statement

Hazard pictograms:

Aerosol, category 1

Extremely flammable aerosol.

Pressurised gas

Contains gas under pressure; may burst if heated.

W508/USA - Ceramic Based Anti-Spatter shield

Carcinogenicity, category 2

Suspected of causing cancer.

Eye irritation, category 2

Causes serious eye irritation.

Specific target organ toxicity - single exposure, category 3

May cause drowsiness or dizziness.



Signal words:

Danger

Hazard statements:

H222 Extremely flammable aerosol.
H280 Contains gas under pressure; may burst if heated.
H351 Suspected of causing cancer.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.

Precautionary statements:

Prevention:

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211 Do not spray on an open flame or other ignition source.
P251 Do not pierce or burn, even after use.
P261 Avoid breathing dust / fume / gas / mist / vapours / spray.
P202 Do not handle until all safety precautions have been read and understood.
P201 Obtain special instructions before use.
P280 Wear protective gloves/ protective clothing / eye protection / face protection.
P271 Use only outdoors or in a well-ventilated area.
P264 Wash hands thoroughly after handling.

Response:

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308+P313 IF exposed or concerned: Get medical advice / attention.
P312 Call a POISON CENTER / doctor / . . . / if you feel unwell.
P337+P313 If eye irritation persists: Get medical advice / attention.
P304+P340 IF INHALED: remove person to fresh air and keep comfortable for breathing.

Storage:

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C / 122°F.
P410+P403 Protect from sunlight. Store in a well-ventilated place.
P403+P233 Store in a well-ventilated place. Keep container tightly closed.
P405 Store locked up.

Disposal:

P501 Dispose of contents / container in compliance with current regulations.

2.2. Other hazards

Information not available

3. Composition/information on ingredients

3.1. Substances

AMBRO-SOL S.R.L.	Revision nr. 1
W508/USA - Ceramic Based Anti-Spatter shield	Dated 4/26/2019
	Printed on 4/26/2019
	Page n. 3/19

Information not relevant

3.2. Mixtures

Contains:

Identification	Conc. %	Classification:
ACETONE		
CAS 67-64-1	52.81	Flammable liquid, category 2 H225, Eye irritation, category 2 H319, Specific target organ toxicity - single exposure, category 3 H336
EC 200-662-2		
INDEX 606-001-00-8		
PROPANE		
CAS 74-98-6	21.35	Flammable gas, category 1 H220, Liquefied gas H280
EC 200-827-9		
INDEX 601-003-00-5		
BUTANE		
CAS 106-97-8	9.15	Flammable gas, category 1 H220, Liquefied gas H280
EC 203-448-7		
INDEX 601-004-00-0		
TITANIUM DIOXIDE		
CAS 13463-67-7	6.1	Carcinogenicity, category 2 H351
EC 236-675-5		
INDEX -		
METHYL ACETATE		
CAS 79-20-9	2.9	Flammable liquid, category 2 H225, Eye irritation, category 2 H319, Specific target organ toxicity - single exposure, category 3 H336
EC 201-185-2		
INDEX 607-021-00-X		
N-BUTYL ACETATE		
CAS 123-86-4	1.8	Flammable liquid, category 3 H226, Specific target organ toxicity - single exposure, category 3 H336
EC 204-658-1		
INDEX 607-025-00-1		
METHANOL		
CAS 67-56-1	0.12	Flammable liquid, category 2 H225, Acute toxicity, category 3 H301, Acute toxicity, category 3 H311, Acute toxicity, category 3 H331, Specific target organ toxicity - single exposure, category 1 H370
EC 200-659-6		
INDEX 603-001-00-X		

The full wording of hazard (H) phrases is given in section 16 of the sheet.

The product is an aerosol containing propellants. For the purposes of calculation of the health hazards, propellants are not considered (unless they have health hazards). The percentages indicated are inclusive of the propellants.

Percentage of propellants: 30.50 %

4. First-aid measures

4.1. Description of first aid measures

AMBRO-SOL S.R.L.	Revision nr. 1 Dated 4/26/2019
W508/USA - Ceramic Based Anti-Spatter shield	Printed on 4/26/2019 Page n. 4/19

EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 15 minutes, opening the eyelids fully. If problem persists, seek medical advice.
SKIN: Remove contaminated clothing. Rinse skin with a shower immediately. Get medical advice/attention immediately. Wash contaminated clothing before using it again.
INHALATION: Remove to open air. If the subject stops breathing, administer artificial respiration. Get medical advice/attention immediately.
INGESTION: Get medical advice/attention immediately. Do not induce vomiting. Do not administer anything not explicitly authorised by a doctor.

4.2. Most important symptoms and effects, both acute and delayed

Specific information on symptoms and effects caused by the product are unknown.

4.3. Indication of any immediate medical attention and special treatment needed

Information not available

5. Fire-fighting measures

5.1. Extinguishing media

SUITABLE EXTINGUISHING EQUIPMENT

The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder and water spray.

UNSUITABLE EXTINGUISHING EQUIPMENT

None in particular.

5.2. Special hazards arising from the substance or mixture

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE

If overheated, aerosol cans can deform, explode and be propelled considerable distances. Put a protective helmet on before approaching the fire. Do not breathe combustion products.

5.3. Advice for firefighters

GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Eliminate all sources of ignition (cigarettes, flames, sparks, etc.) from the leakage site. Send away individuals who are not suitably equipped. Wear protective gloves / protective clothing / eye protection / face protection.

6.2. Environmental precautions

Do not disperse in the environment.

6.3. Methods and material for containment and cleaning up

Use inert absorbent material to soak up leaked product. Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

AMBRO-SOL S.R.L.	Revision nr. 1 Dated 4/26/2019
W508/USA - Ceramic Based Anti-Spatter shield	Printed on 4/26/2019 Page n. 5/19

6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

7. Handling and storage

7.1. Precautions for safe handling

Avoid bunching of electrostatic charges. Do not spray on flames or incandescent bodies. Vapours may catch fire and an explosion may occur; vapour accumulation is therefore to be avoided by leaving windows and doors open and ensuring good cross ventilation. Do not eat, drink or smoke during use. Do not breathe spray.

7.2. Conditions for safe storage, including any incompatibilities

Store in a place where adequate ventilation is ensured, away from direct sunlight at a temperature below 50°C / 122°F, away from any combustion sources.

7.3. Specific end use(s)

Information not available

8. Exposure controls/personal protection

8.1. Control parameters

Regulatory References:

USA	NIOSH-REL	NIOSH publication No. 2005-149, 3th printing, 2007.
USA	OSHA-PEL	Occupational Exposure Limits - Limits for Air Contaminants TABLE Z-1-1910.1000.
USA	CAL/OSHA-PEL	California Division of Occupational Safety and Health (Cal-OSHA) Permissible Exposure Limits (PELs).
EU	OEL EU	Directive (EU) 2017/2398; Directive (EU) 2017/164; Directive 2009/161/EU; Directive 2006/15/EC; Directive 2004/37/EC; Directive 2000/39/EC; Directive 91/322/EEC.
	TLV-ACGIH	ACGIH 2018

ACETONE

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min	
		mg/m3	ppm	mg/m3	ppm
TLV-ACGIH	-	250		500	
OEL	EU	1210	500		
OSHA	USA	2400	1000		
CAL/OSHA	USA	1200	500	1780 (C)	3000 (C)
NIOSH	USA	590	250		

PROPANE

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min	
		mg/m3	ppm	mg/m3	ppm
TLV-ACGIH	-		1000		
OSHA	USA	1800	1000		
CAL/OSHA	USA	1800	1000		

AMBRO-SOL S.R.L.					Revision nr. 1	
W508/USA - Ceramic Based Anti-Spatter shield					Dated 4/26/2019	
					Printed on 4/26/2019	
Page n. 6/19						
NIOSH	USA	1800	1000			
BUTANE						
Threshold Limit Value						
Type	Country	TWA/8h	STEL/15min			
		mg/m3	ppm	mg/m3	ppm	
TLV-ACGIH	-		1000			
CAL/OSHA	USA	1.9	800			
NIOSH	USA	1900	800			
TITANIUM DIOXIDE						
Threshold Limit Value						
Type	Country	TWA/8h	STEL/15min			
		mg/m3	ppm	mg/m3	ppm	
TLV-ACGIH	-	10				
OSHA	USA	15	INHAL			
CAL/OSHA	USA	10	INHAL			
CAL/OSHA	USA	5	RESP			
METHYL ACETATE						
Threshold Limit Value						
Type	Country	TWA/8h	STEL/15min			
		mg/m3	ppm	mg/m3	ppm	
TLV-ACGIH	-	606	200	757	250	
OSHA	USA	610	200			
CAL/OSHA	USA	610	200	760	250	
NIOSH	USA	610	200	760	250	
N-BUTYL ACETATE						
Threshold Limit Value						
Type	Country	TWA/8h	STEL/15min			
		mg/m3	ppm	mg/m3	ppm	
TLV-ACGIH	-	713	150	950	200	
OSHA	USA	710	150			
CAL/OSHA	USA	710	150	950	200	
NIOSH	USA	710	150	950	200	
XYLENE (MIXTURE OF ISOMERS)						
Threshold Limit Value						
Type	Country	TWA/8h	STEL/15min			
		mg/m3	ppm	mg/m3	ppm	
TLV-ACGIH	-	434	100	651	150	
OEL	EU	221	50	442	100	SKIN
OSHA	USA	435	100			
CAL/OSHA	USA	435	100	655 (C)	3000 (C)	
2-METHOXY-1-METHYLETHYL ACETATE						
Threshold Limit Value						

AMBRO-SOL S.R.L.				Revision nr. 1		
W508/USA - Ceramic Based Anti-Spatter shield				Dated 4/26/2019		
				Printed on 4/26/2019		
				Page n. 7/19		

Type	Country	TWA/8h		STEL/15min		
		mg/m3	ppm	mg/m3	ppm	
OEL	EU	275	50	550	100	SKIN
CAL/OSHA	USA	541	100	811	150	SKIN

Methyl formed

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		
		mg/m3	ppm	mg/m3	ppm	
TLV-ACGIH	-	246	100	0	0	
OSHA	USA	250	100			
CAL/OSHA	USA	250	100	375	150	
NIOSH	USA	250	100	375	150	

METHANOL

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		
		mg/m3	ppm	mg/m3	ppm	
TLV-ACGIH	-	262	200	328	250	
OEL	EU	260	200			SKIN
OSHA	USA	260	200			
CAL/OSHA	USA	260	200	325 (C)	1000 (C)	SKIN
NIOSH	USA	260	200	325	250	SKIN

Legend:

(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction.

TLV of solvent mixture: 264 mg/m3

8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration. Personal protective equipment must comply with current regulations.

HAND PROTECTION

None required.

SKIN PROTECTION

Wear category I professional long-sleeved overalls and safety footwear. Wash body with soap and water after removing protective clothing.

EYE PROTECTION

Wear airtight protective goggles (OSHA 29 CFR 1910.133).

RESPIRATORY PROTECTION

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, a mask with a NIOSH certified combined filter should be worn (NIOSH 42 CFR 84, OSHA 29 CFR 1910.134).

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold

values considered. The protection provided by masks is in any case limited.

ENVIRONMENTAL EXPOSURE CONTROLS

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

9. Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance	aerosol
Colour	colourless
Odour	characteristic of solvent
Odour threshold	Not available
pH	Not available
Melting point / freezing point	Not available
Initial boiling point	Not available
Boiling range	Not available
Flash point	< 0 °C
Evaporation Rate	Not available
Flammability of solids and gases	flammable gas
Lower inflammability limit	Not available
Upper inflammability limit	Not available
Lower explosive limit	Not available
Upper explosive limit	Not available
Vapour pressure	Not available
Vapour density	Not available
Relative density	0.73 g/ml
Solubility	insoluble in water
Partition coefficient: n-octanol/water	Not available
Auto-ignition temperature	Not available
Decomposition temperature	Not available
Viscosity	Not available
Explosive properties	not applicable
Oxidising properties	not applicable

9.2. Other information

Total solids (250°C / 482°F)	10,80 %
VOC :	36,66 % - 0,00 g/litre
Solvent base	Acetone

10. Stability and reactivity

10.1. Reactivity

There are no particular risks of reaction with other substances in normal conditions of use.

N-BUTYL ACETATE

Decomposes on contact with: water.

10.2. Chemical stability

The product is stable in normal conditions of use and storage.

10.3. Possibility of hazardous reactions

<p style="text-align: center;">AMBRO-SOL S.R.L.</p>	<p>Revision nr. 1</p> <p>Dated 4/26/2019</p>
<p style="text-align: center;">W508/USA - Ceramic Based Anti-Spatter shield</p>	<p>Printed on 4/26/2019</p> <p>Page n. 9/19</p>

No hazardous reactions are foreseeable in normal conditions of use and storage.

ACETONE

Risk of explosion on contact with: bromine trifluoride,fluorine dioxide,hydrogen peroxide,nitrosyl chloride,2-methyl-1,3 butadiene,nitromethane,nitrosyl perchlorate.May react dangerously with: potassium tert-butoxide,alkaline hydroxides,bromine,bromoform,isoprene,sodium,sulphur dioxide,chromium trioxide,chromyl chloride,nitric acid,chloroform,peroxymonosulphuric acid,phosphoryl oxychloride,chromosulphuric acid,fluorine,strong oxidising agents,strong reducing agents.Develops flammable gas on contact with: nitrosyl perchlorate.

N-BUTYL ACETATE

Risk of explosion on contact with: strong oxidising agents.May react dangerously with: alkaline hydroxides,potassium tert-butoxide.Forms explosive mixtures with: air.

10.4. Conditions to avoid

Avoid overheating.

ACETONE

Avoid exposure to: sources of heat,naked flames.

N-BUTYL ACETATE

Avoid exposure to: moisture,sources of heat,naked flames.

10.5. Incompatible materials

Strong reducing or oxidising agents, strong acids or alkalis, hot material.

ACETONE

Incompatible with: acids,oxidising substances.

N-BUTYL ACETATE

Incompatible with: water,nitrates,strong oxidants,acids,alkalis,zinc.

10.6. Hazardous decomposition products

ACETONE

May develop: ketenes,irritant substances.

AMBRO-SOL S.R.L.	Revision nr. 1
W508/USA - Ceramic Based Anti-Spatter shield	Dated 4/26/2019
	Printed on 4/26/2019
	Page n. 10/19

11. Toxicological information

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification.

It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

11.1. Information on toxicological effects

Metabolism, toxicokinetics, mechanism of action and other information

Information not available

Information on likely routes of exposure

N-BUTYL ACETATE

WORKERS: inhalation; contact with the skin.

METHANOL

WORKERS: inhalation; contact with the skin.

POPULATION: ingestion of contaminated food or water; contact with the skin of products containing the substance.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

N-BUTYL ACETATE

In humans, the substance's vapours cause irritation of the eyes and nose. In the event of repeated exposure, skin irritation, dermatitis (dryness and cracking of the skin) and keratitis appear.

METHANOL

The minimum lethal dose for humans by ingestion is considered to be in the range from 300 to 1000 mg/kg. Ingestion of 4-10 ml of the substance may cause permanent blindness in adult humans (IPCS).

Interactive effects

N-BUTYL ACETATE

A case of acute intoxication been reported involving a 33 year old worker while cleaning a tank with a preparation containing xylenes, butyl acetate and ethylene glycol acetate. The person had irritation of the conjunctiva and upper respiratory tract, drowsiness and motor coordination disorders, which disappeared within 5 hours. The symptoms are attributed to poisoning by mixed xylenes and butyl acetate, with a possible synergistic effect responsible for the neurological effects. Cases of vacuolar keratitis are reported in workers exposed to a mixture of butyl acetate and isobutanol vapours, but with uncertainty concerning the responsibility of a particular solvent (INRC, 2011).

ACUTE TOXICITY

TITANIUM DIOXIDE

LD50 (Oral) > 10000 mg/kg Rat

N-BUTYL ACETATE

LD50 (Oral) > 6400 mg/kg Rat

W508/USA - Ceramic Based Anti-Spatter shield

LD50 (Dermal) > 5000 mg/kg Rabbit

LC50 (Inhalation) 21.1 mg/l/4h Rat

SKIN CORROSION / IRRITATION

Repeated exposure may cause skin dryness or cracking.
Does not meet the classification criteria for this hazard class

SERIOUS EYE DAMAGE / IRRITATION

Causes serious eye irritation

RESPIRATORY OR SKIN SENSITISATION

Does not meet the classification criteria for this hazard class

GERM CELL MUTAGENICITY

Does not meet the classification criteria for this hazard class

CARCINOGENICITY

Suspected of causing cancer

Carcinogenicity Assessment:

67-64-1ACETONE

ACGIH:: A4

13463-67-7TITANIUM DIOXIDE

ACGIH:: A4

IARC:2B

1330-20-7XYLENE (MIXTURE OF ISOMERS)

ACGIH:: A4

IARC:3

REPRODUCTIVE TOXICITY

Does not meet the classification criteria for this hazard class

STOT - SINGLE EXPOSURE

May cause drowsiness or dizziness

STOT - REPEATED EXPOSURE

Does not meet the classification criteria for this hazard class

ASPIRATION HAZARD

Does not meet the classification criteria for this hazard class

12. Ecological information

Use this product according to good working practices. Avoid littering. Inform the competent authorities, should the product reach waterways or contaminate soil or vegetation.

12.1. Toxicity

Information not available

12.2. Persistence and degradability

PROPANE

Global Warming Potential (GWP): 3. Ozone Depletion Potential (ODP): 0.

TITANIUM DIOXIDE

Solubility in water < 0.001 mg/l

Degradability: information not available

BUTANE

Solubility in water 0.1 - 100 mg/l

Rapidly degradable

PROPANE

Solubility in water 0.1 - 100 mg/l

Rapidly degradable

METHANOL

Solubility in water 1000 - 10000 mg/l

Rapidly degradable

ACETONE

Rapidly degradable

METHYL ACETATE

Solubility in water 243500 mg/l

Rapidly degradable

N-BUTYL ACETATE

Solubility in water 1000 - 10000 mg/l

12.3. Bioaccumulative potential

BUTANE

Partition coefficient: n-octanol/water 1.09

PROPANE

Partition coefficient: n-octanol/water 1.09

W508/USA - Ceramic Based Anti-Spatter shield**METHANOL**

Partition coefficient: n-octanol/water -0.77

BCF 0.2

ACETONE

Partition coefficient: n-octanol/water -0.23

BCF 3

METHYL ACETATE

Partition coefficient: n-octanol/water 0.18

N-BUTYL ACETATE

Partition coefficient: n-octanol/water 2.3

BCF 15.3

12.4. Mobility in soil**METHYL ACETATE**

Partition coefficient: soil/water 0.18

N-BUTYL ACETATE

Partition coefficient: soil/water < 3

12.5. Results of PBT and vPvB assessment

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

12.6. Other adverse effects

Information not available

13. Disposal considerations**13.1. Waste treatment methods**

Reuse, when possible. Neat product residues should be considered special non-hazardous waste.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

Waste from this product may be hazardous as defined under the Resource Conservation and Recovery Act (RCRA).

Waste must be tested for ignitability to determine the applicable EPA hazardous waste numbers.

Do not puncture or incinerate containers, even empty. Do not allow to enter waterways, wastewater, soil, storm drains or sewer systems. Dispose of in accordance with Federal, State/Provincial, and Local regulations regarding pollution.

14. Transport information**14.1. UN number**

AMBRO-SOL S.R.L.	Revision nr. 1
W508/USA - Ceramic Based Anti-Spatter shield	Dated 4/26/2019
	Printed on 4/26/2019
	Page n. 14/19

ADR / RID, IMDG, 1950
IATA:

14.2. UN proper shipping name

ADR / RID: AEROSOLS
IMDG: AEROSOLS
IATA: AEROSOLS, FLAMMABLE

14.3. Transport hazard class(es)

ADR / RID: Class: 2 Label: 2.1
IMDG: Class: 2 Label: 2.1
IATA: Class: 2 Label: 2.1



14.4. Packing group

ADR / RID, IMDG, -
IATA:

14.5. Environmental hazards

ADR / RID: NO
IMDG: NO
IATA: NO

14.6. Special precautions for user

ADR / RID:	HIN - Kemler: --	Limited Quantities: 1 L	Tunnel restriction code: (D)
IMDG:	Special Provision: - EMS: F-D, S-U	Limited Quantities: 1 L	
IATA:	Cargo:	Maximum quantity: 150 Kg	Packaging instructions: 203
	Pass.:	Maximum quantity: 75 Kg	Packaging instructions: 203
	Special Instructions:	A145, A167, A802	

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Information not relevant

15. Regulatory information

W508/USA - Ceramic Based Anti-Spatter shield

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixtureU.S. Federal RegulationsTSCA:Clean Air Act Section 112(b):

1330-20-7

XYLENE (MIXTURE OF ISOMERS)

67-56-1

METHANOL

Clean Air Act Section 602 Class I Substances:

No component(s) listed.

Clean Air Act Section 602 Class II Substances:

No component(s) listed.

Clean Water Act –
Priority Pollutants:

No component(s) listed.

Clean Water Act –
Toxic Pollutants:

No component(s) listed.

DEA List I Chemicals (Precursor Chemicals):

No component(s) listed.

DEA List II Chemicals (Essential Chemicals):EPA List of Lists:

313 Category Code:

67-64-1

ACETONE

1330-20-7

XYLENE (MIXTURE OF ISOMERS)

67-56-1

METHANOL

EPCRA 302 EHS TPQ:

No component(s) listed.

EPCRA 304 EHS RQ:

No component(s) listed.

CERCLA RQ:

AMBRO-SOL S.R.L.	Revision nr. 1
	Dated 4/26/2019
W508/USA - Ceramic Based Anti-Spatter shield	Printed on 4/26/2019
	Page n. 16/19

67-64-1	ACETONE
123-86-4	N-BUTYL ACETATE
1330-20-7	XYLENE (MIXTURE OF ISOMERS)
67-56-1	METHANOL

EPCRA 313 TRI:

1330-20-7	XYLENE (MIXTURE OF ISOMERS)
67-56-1	METHANOL

RCRA Code:

67-64-1	ACETONE
1330-20-7	XYLENE (MIXTURE OF ISOMERS)
67-56-1	METHANOL

CAA 112 (r) RMP TQ:

74-98-6	PROPANE (Alkanes, Alkanes (aliphatic hrydrocarbon alkanes, C1- C4))
106-97-8	BUTANE (Alkanes)
107-31-3	Methyl formed

State Regulations

Massachussetts:

67-64-1	ACETONE
74-98-6	PROPANE (Alkanes, Alkanes (aliphatic hrydrocarbon alkanes, C1- C4))
106-97-8	BUTANE (Alkanes)
13463-67-7	TITANIUM DIOXIDE (Titanium dioxide (airborne, unbound particles of respirable size))
79-20-9	METHYL ACETATE
123-86-4	N-BUTYL ACETATE
1330-20-7	XYLENE (MIXTURE OF ISOMERS)
107-31-3	Methyl formed
67-56-1	METHANOL

Minnesota:

67-64-1	ACETONE
74-98-6	PROPANE (Alkanes, Alkanes (aliphatic hrydrocarbon alkanes, C1- C4))
106-97-8	BUTANE (Alkanes)
13463-67-7	TITANIUM DIOXIDE (Titanium dioxide (airborne, unbound particles of respirable size))
79-20-9	METHYL ACETATE
123-86-4	N-BUTYL ACETATE
1330-20-7	XYLENE (MIXTURE OF ISOMERS)
107-31-3	Methyl formed
67-56-1	METHANOL

New Jersey:

AMBRO-SOL S.R.L.	Revision nr. 1 Dated 4/26/2019
W508/USA - Ceramic Based Anti-Spatter shield	Printed on 4/26/2019 Page n. 17/19

67-64-1	ACETONE
74-98-6	PROPANE (Alkanes, Alkanes (aliphatic hydrocarbon alkanes, C1- C4))
106-97-8	BUTANE (Alkanes)
13463-67-7	TITANIUM DIOXIDE (Titanium dioxide (airborne, unbound particles of respirable size))
79-20-9	METHYL ACETATE
123-86-4	N-BUTYL ACETATE
1330-20-7	XYLENE (MIXTURE OF ISOMERS)
107-31-3	Methyl formed
67-56-1	METHANOL

New York:

67-64-1	ACETONE
123-86-4	N-BUTYL ACETATE
1330-20-7	XYLENE (MIXTURE OF ISOMERS)
67-56-1	METHANOL

Pennsylvania:

67-64-1	ACETONE
74-98-6	PROPANE (Alkanes, Alkanes (aliphatic hydrocarbon alkanes, C1- C4))
106-97-8	BUTANE (Alkanes)
13463-67-7	TITANIUM DIOXIDE (Titanium dioxide (airborne, unbound particles of respirable size))
79-20-9	METHYL ACETATE
123-86-4	N-BUTYL ACETATE
1330-20-7	XYLENE (MIXTURE OF ISOMERS)
107-31-3	Methyl formed
67-56-1	METHANOL

California:

67-64-1	ACETONE
106-97-8	BUTANE (Alkanes)
79-20-9	METHYL ACETATE
123-86-4	N-BUTYL ACETATE
1330-20-7	XYLENE (MIXTURE OF ISOMERS)
107-31-3	Methyl formed
67-56-1	METHANOL

Proposition 65:

WARNING! This product contains chemicals known to the State of California to cause cancer and birth defects or reproductive harm.

13463-67-7	TITANIUM DIOXIDE C (Titanium dioxide (airborne, unbound particles of respirable size))
67-56-1	METHANOL D

W508/USA - Ceramic Based Anti-Spatter shield

International Regulations

Substances subject to exportation reporting pursuant to (EC) Reg. 649/2012:

None

Substances subject to the Rotterdam Convention:

None

Substances subject to the Stockholm Convention:

None

Canadian WHMIS

Information not available

16. Other information

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

H220	Extremely flammable gas.
H222	Extremely flammable aerosol.
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H280	Contains gas under pressure; may burst if heated.
H351	Suspected of causing cancer.
H301	Toxic if swallowed.
H311	Toxic in contact with skin.
H331	Toxic if inhaled.
H370	Causes damage to organs.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.

LEGEND:

- 313 CATEGORY CODE: Emergency Planning and Community Right-to Know Act Section 313 Category Code
- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- CAA 112 ® RMP TQ: Risk Management Plan Threshold Quantity (Clean Air Act Section 112®)
- CAS NUMBER: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CERCLA RQ: Reportable Quantity (Comprehensive Environment Response, Compensation, and Liability Act)
- CLP: EC Regulation 1272/2008
- DEA: Drug Enforcement Administration
- EmS: Emergency Schedule
- EPA: US Environmental Protection Agency
- EPCRA: Emergency Planning and Community Right-to Know Act
- EPCRA 302 EHS TPQ: Extremely Hazardous Substance Threshold Planning Quantity (Section 302 Category Code)
- EPCRA 304 EHS RQ: Extremely Hazardous Substance Reportable Quantity (Section 304 Category Code)
- EPCRA 313 TRI: Toxics Release Inventory (Section 313 Category Code)
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- LC50: Lethal Concentration 50%

AMBRO-SOL S.R.L.	Revision nr. 1 Dated 4/26/2019
W508/USA - Ceramic Based Anti-Spatter shield	Printed on 4/26/2019 Page n. 19/19

- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PEL: Predicted exposure level
- RCRA Code: Resource Conservation and Recovery Act Code
- REL: Recommended exposure limit
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TSCA: Toxic Substances Control Act
- TWA STEL: Short-term exposure limit
- TWA: Time-weighted average exposure limit
- VOC: Volatile organic Compounds
- WHMIS: Workplace Hazardous Materials Information System.

GENERAL BIBLIOGRAPHY:

- GHS rev. 3
- The Merck Index. 10th Edition
- Handling Chemical Safety
- Niosh - Registry of Toxic Effects of Chemical Substances
- INRS - Fiche Toxicologique (toxicological sheet)
- Patty - Industrial Hygiene and Toxicology
- N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition
- ECHA website
- Database of SDS models for chemicals - Ministry of Health and ISS (Istituto Superiore di Sanità) - Italy
- 6 NYCRR part 597
- Cal/OSHA website
- California Safe Drinking Water and Toxic Enforcement Act
- EPA website
- Hazard Communication Standard (HCS 2012)
- IARC website
- List Of Lists EPA: Consolidated List of Chemicals Subject to EPCRA, CERCLA and Section 112® of the Clean Air Act
- Massachussetts 105 CMR Department of public health 670.000: "Right to Know"
- Minensota Chapter 5206 Departemnt Of Labor and Industry Hazardous Substances, Employee "Right to Know".
- New Jersey Worker and Community Right to know Act N.J.S.A.
- NTP. 2011. Report on Carcinogens, 12th Edition.
- OSHA website
- Pennsylvania, Hazardous Substance List, Chapter 323

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.