



Multipurpose Acrylic Spray Paint RAL (V400)

It's very difficult to replicate the properties of this Ambro-Sol spray paint. It has brilliant power and sheen, great for interiors and exterior. It can be used on various surfaces. It dries in minutes... what else? It's MADE IN ITALY!!

ACRYLIC SPRAY PAINT- A multi-purpose paint designed for indoor and outdoor use. It can be used on various surfaces including wood, metal, glass, ceramic, plastering, masonry, doors, furniture, radiators, ornaments, and other objects.



Product subject to directive C.O.V.
Subcategory: Special finishes
Limit value COV: 840 g/liter

FIELDS OF APPLICATION:

Wood surfaces, metal surfaces as iron, aluminum, steel, glass and plastics.

TECHNICAL SPECIFICATIONS:

Quantity	400 ml – Net Wt. 10.3 oz 295 g
Case	6 pieces
Aspect	Cylinder containing under pressure fluid
Chemical nature	Very fast drying acrylic paints
Color	Various
Odor	Characteristic of solvent
Relative density	At 68°F 0.72 ÷ 0.76 g/ml
Flash point	Low. 32°F
Writing on spray bottom	Barcode, production date, product name
Pressure	at 68°F 5.5 ± 0.5 bar
Pressure	at 122°F 8.0 ± 0.5 bar
Viscosity Ford cup	From 10" to 13"
Dry residual in spray	From 15% to 22%
Granulometry grindometer	Bottom Scale 0 a 2 Micron
Gloss	From 7 to 95 Gloss (Glossmeter angle 60°)
Thickness 1 hand	about 13 Micron
Thickness 3 hands	about 36 Micron
Resistance temperature	14°F / 212°F (Peak 248°F)
Drying time t=68°F:	Out dust 10 minutes
	Dry to touch 15 minutes
	Dry in depth 22 hours
Security cap child-proof patented and registered	
Token references color	
Is possible have different type of actuators for various effects and employ	

FOR A PROFESSIONAL RESULT: Clean the surface with a suitable solvent/detergent. If there is paint or rust, remove with wire brush/sand paper. Surfaces previously painted must be uniform. A smooth, stiff, or glossy surface may need to be lightly sanded to create better adhesion for paint being applied.

Iron surfaces: enamel anti-rust V400PAST.1, V400PAST.9, V400PAST.10, V400STUCCO, V400PRIMER.3, V400PRIMER.4)

Galvanized surfaces: galvanized sheets primer (V400PRIMER.5)

Metallic surfaces and light alloy: Anchor metals and alloy primer (V400PRIMER.1)

Plastic surfaces: anchor primer for plastics (V400PRIMER.2)

Iron surfaces and metallic exposed to higher risk of oxidation: Zincs (Z350, Z351, Z355, Z353, Z352, Z358, Z356, and Z359)

Metallic surfaces and light alloy under UV ray and extreme conditions: V400PRIMER2, V400PRIMER.5 or only V400 acrylic.

HOW TO USE:


- Vigorously shake the can for at least 1 minute, until the inner marbles move freely. It is also suggested to occasionally shake the can during use.
- Carefully clean the surface before application.
- Test in a hidden area to verify compatibility of the surface with the paint.

**PAINT CAP**

Remove the three secure seals on sides

**SPRAY APPLICATION:**

- Apply a light first coat to improve coverage and adherence. Apply from a distance of 8-10 inches.
- After a few moments; Apply a second horizontal coat, immediately followed by a third vertical coat
- Leave to dry
- After use, it's advisable to spray for 2/3 seconds with the can upside down. This will prevent the dispenser from clogging.
- After 24 hours proceed with the normal use of painted piece.

**EROGATORE PRODOTTI
VERNICIANTI NERO/BIANCO
BLACK/WHITE PAINTING
PRODUCTS ACTUATOR**

Dispensing: linear

**Quantity product dispensed:
low**

Dispensing type: medium cone

Spray type: nebulized

STORAGE

Before using: Stock the product in a dry location above 40°F degrees and below 113°F. After use, keep containers closed. In the original package, the product can be conserved for 24 months.

After the first use: conserve in a fresh and dry location, away from hot conditions. Keep out of reach of children.

Hazards identification:

H222	Extremely flammable aerosol.
H229	Pressurized container: may burst if heated.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness
EUH066	Repeated exposure may cause skin dryness or cracking.

This information, even if reliable, must be considered only approximate. We are not responsible for the wrong use of the product, or the violation of any license. Before using, the users should verify the suitability of the product for its specific use.