



SILICONE SPRAY (OL103)

This spray has a strong lubricating and protective power. It is water repellent and protects against wear.



HOW TO USE: Shake and spray directly on the parts to be treated. This product can also be used with the straw attached to the cap.

Quantity	400 ml – Net Wt. 9.3 oz 265 g
Barcode	EAN 13: 8034108890142
Case	12 pieces

SILICONE SPRAY – A lubricating spray with a pure silicone oil base and anti-stick release agents. It is water repellent, protects against wear, and prevents the accumulation of electrostatic charges. It also protects seals from cracking, increasing tightness and durability.

Technical Specifications:

Aspect	Cylinder containing under pressure fluid
Color	Colorless
Odor	Characteristic of solvent
Relative density	a 68°F 0.62 ÷ 0.66 g/ml
Flash point	Low.32° F
Pressure at 68°F	4/6 bar
Silicone Viscosity	350 - 400 mm ² /s a 77°F
Auto ignition temperature	>752°F (data per the dry residual)
Steam pressure	<0.01 kPa a 68°F
Freezing point	ca -58°F
Water solubility	Insoluble

STORAGE

Before using: Stock the product in a dry location above 32°F degrees and below 113°F. After use, keep containers closed. In the original package, the product can be conserved for 24 months.

After the first use: conserve in a fresh and dry location, away from hot conditions. Keep out of reach of children.

Hazards identification:

H222	Extremely flammable aerosol.
H229	Pressurized container: it may burst if heated.
H315	Causes skin irritation.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.

This information, even if reliable, must be considered only approximate. We are not responsible for the wrong use of the product, or the violation of any license. Before using, the users should verify the suitability of the product for its specific use.